

YX7-3AC

高压旋涡气泵性能参数YX-71/79

H 系列

漩涡式气泵在真空和压力操作的选型和订购参数。

订购型号 • 有库存	马 达				重量 kg	噪音 dB(A)	最大流量 m ³ /h	最高真空 mbar	最高压力 mbar	真空阀
	额 定			电 流 A						类型 × 型号
	输出功率 KW	电 压 V	电 流 A							
HZ	KW	V	A	kg	dB(A)	m ³ /h	mbar	mbar		
• YX-71D-1	50	1.6	200-240 △ /345-415	8.5 △ /4.9Y	27	69	330	-160	150	1x...2110/...2145
	60	2.05	220-275 △ /380-480	8.8 △ /5.1Y		72	380	-160	150	1x...2114/...2146
• YX-71D-2	50	2.2	200-240 △ /345-415	9.7 △ /5.6Y	30	69	330	-210	200	1x...2110/...2145
	60	2.55	220-275 △ /380-480	10.3 △ /6.0Y		72	380	-210	200	1x...2114/...2146
• YX-71D-3	50	3.0	200-240 △ /345-415	12.5 △ /7.2Y	36	69	330	-270	290	1x...2110/...2145
	60	3.45	220-275 △ /380-480	12.6 △ /7.3Y		72	380	-250	230	1x...2114/...2146
• YX-71D-4	50	4.0	345-415 △ /600-720	9.0 △ /5.2Y	40	69	330	-290	330	1x...2110/...2145
	60	4.6	380-480 △ /660-720	9.0 △ /5.2Y		72	380	-230	330	1x...2114/...2146
• YX-72S-1	50	2.2	200-240 △ /345-415	9.7 △ /5.6Y	43	73	320	-220	210	1x2Bx2110/...2145
	60	2.55	220-275 △ /380-480	10.3 △ /6.0Y		76	380	-170	150	2x2Bx2114/...2146
• YX-72S-2	50	3.0	200-240 △ /345-415	12.5 △ /7.2Y	48	73	320	-280	260	1x2Bx2110/...2145
	60	3.45	220-275 △ /380-480	12.6 △ /7.3Y		76	380	-230	200	2x2Bx2114/...2146
• YX-72S-3	50	4.3	345-415 △ /600-720	10.0 △ /5.2Y	54	73	320	-360	380	1x2Bx2110/...2145
	60	4.8	380-480 △ /660-720	10.4 △ /6.0Y		76	380	-350	320	1x2Bx2114/...2146
• YX-72S-4	50	5.5	345-415 △ /600-720	13.3 △ /7.7Y	66	73	320	-440	500	1x2Bx2110/...2145
	60	6.3	380-480 △ /660-720	13.3 △ /7.7Y		76	380	-440	500	1x2Bx2114/...2146
• YX-72S-5	50	7.5	345-415 △ /600-720	16.7 △ /9.6Y	73	73	320	-440	570	1x2Bx2110/...2145
	60	8.6	380-480 △ /660-720	17.3 △ /10.0Y		76	380	-460	660	1x2Bx2114/...2146
• YX-73D-1	50	1.6	200-240 △ /345-415	8.5 △ /4.9Y	29	70	420	-100	100	1x...2110/...2145
	60	2.05	220-275 △ /380-480	8.8 △ /5.1Y		73	500	-110	80	3x...2114/...2146
• YX-73D-2	50	2.2	200-240 △ /345-415	9.7 △ /5.6Y	32	70	420	-170	170	1x...2110/...2145
	60	2.55	220-275 △ /380-480	10.3 △ /6.0Y		73	500	-160	120	2x...2114/...2146
• YX-73D-3	50	3.0	200-240 △ /345-415	12.5 △ /7.2Y	37	70	420	-220	220	1x...2110/...2145
	60	3.45	220-275 △ /380-480	12.6 △ /7.3Y		73	500	-200	190	2x...2114/...2146
• YX-73D-4	50	4.0	345-415 △ /600-720	9.0 △ /5.2Y	43	70	420	-260	310	1x...2110/...2145
	60	4.6	380-480 △ /660-720	9.0 △ /5.2Y		73	500	-260	280	2x...2114/...2146
• YX-74S-1	50	4.0	345-415 △ /600-720	9.0 △ /5.2Y	54	74	500	-150	140	1x2Bx2110/...2145
	60	4.6	380-480 △ /660-720	9.0 △ /5.2Y		78	600	-100	90	2x2Bx2114/...2146
• YX-74S-2	50	5.5	345-415 △ /600-720	13.3 △ /7.7Y	69	74	500	-240	260	1x2Bx2110/...2145
	60	6.3	380-480 △ /660-720	13.3 △ /7.7Y		78	600	-210	200	2x2Bx2114/...2146
• YX-74S-3	50	7.5	345-415 △ /600-720	16.7 △ /9.6Y	75	74	500	-240	320	1x2Bx2110/...2145
	60	8.6	380-480 △ /660-720	17.3 △ /10.0Y		78	600	-270	300	1x2Bx2114/...2146
• YX-79D-1	50	2.2	200-240 △ /345-415	12.5 △ /7.2Y	36	69	320	-160	200	-
	60	3.45	220-275 △ /380-480	12.6 △ /7.3Y		72	370	-240	250	-